

Fully Isolated Limited Distance Modem, RS-232/485 Converter



- ✓ Complete Isolation with Optical Couplers and Power DC-to-DC Converter
- ✓ Industrial Surge Protection Devices
- ✓ Six LED Diagnostic Indicators
- ✓ 19.2K Baud at 3 Miles (5KM), 57.6K Baud at 0.5 Miles (0.8KM)
- ✓ Request-to-Send, Clear-to-Send Handshake
- ✓ Tri-State Outputs for Multidrop Applications, up to 64 Devices
- ✓ Selection of Connectors
- ✓ Wide Operating Temperature Range
- ✓ Solderless Screw Terminal Field Connections

The LDM485 is a compact RS-232 to RS-485 converter which features a complete electrical isolation barrier and heavy duty electrical surge protectors. These devices feature a rugged aluminum enclosure small enough to mount on the back panel of typical computer equipment, saving valuable desk and floor space. Isolation is provided by optical couplers and a DC-to-DC converter. The RS-232 connection is through male or female EIA 25-pin connectors. The RS-485 connections are made through convenient solderless screw terminals.

The LDM485 series is designed for full duplex operation over two-wire pairs. Outputs are tri-state, allowing multidropping of up to 64 units. Hardware handshake is available over two separate wire pairs. Data rates are DC to 57.6k baud. Six diagnostic LED indicators are provided (see Figure 1) for installation guidance and system troubleshooting. The RS-232



\$225
Basic Unit

LDM485-P, \$225, shown smaller than actual size

interface supports Request To Send, Clear To Send, Data Set Ready, Received Line Signal Detect, and Data Terminal Ready. A convenient null modem switch is provided for the data lines. Also, a line termination switch connects a line termination resistor and line bias resistors to the RS-485 receive lines. The RS-485 interface supports Request To Send and Clear To Send on separate wire pairs. The LDM485 may be used to convert two sets of send and receive channels by using RTS and CTS circuits as the second data channels. Data rates are the same. The units use 12VAC from a wall-mounted transformer to screw terminals 1 and 2 on the RS-485 connector. Alternately, they can use ± 12 VDC to pins 9 (+) and 10 (-) of the RS-232 connector.

The LDM485 conforms to EIA RS-232 and RS-485 specifications. Data Terminal Ready must be asserted by the host RS-232 port

before the LDM485 can transmit data. When Data Terminal Ready is not asserted, all outputs of the LDM485 are high impedance, allowing up to 64 LDM485 units to be multidropped on a common communications cable. See Figures 1 and 3 for details.

Request To Send and Clear To Send are carried through the RS-485 port as two separate wire pairs. These may be used for full duplex flow control.

Data Terminal Ready, DTR, must be asserted before the LDM485 can transmit data. This is normally done by the host computer. For situations where the host equipment does not have the capability of supplying a DTR signal, RLSD may be used to automatically assert DTR. On the RS-232 connector P1 of each LDM485, simply connect RLSD pin 8 to DTR pin 20. This connection is not appropriate for multi-drop installations.

SPECIFICATIONS

Model	LDM485					
Baud Rate Range	0 – 57.6K					
Baud Rate	57.6K	38.4K	19.2K	9.6K	4.8K	2.4K – 0
Distance (miles)⁽¹⁾	0.5	1	3	4	5	8
Distance (km)	0.8	1.7	5	6.7	8.3	13.3
Wire Capacitance	Equal to 25pF per foot and up to 32 multidrop units					
Maximum Multidrop Units	64					
Common Mode Isolation	Surge: 1500V Continuous: 1000V					
Differential Mode Surge Protection (9 devices)	(AC input) ANSI/IEEE C37.90.1-1989 (all RS-485 inputs and outputs)					
Modes	Asynchronous 4-wire duplex, 2-wire half-duplex, 2-wire simplex					

Notes: (1) Distances reduced if multidropping more than 32 units; by 30% for 33-48 units, 50% for 49-64.



RS-232 P1 Pin	Descriptions	RS-485 P2 Pin Descriptions
Pin 1	Case	Case Ground Pin 1
Pin 2	TD	12VAC PWR RTN
Pin 3	RD	Transmit Data Pin 2 TD A
Pin 4	RTS	Receive Data Pin 3 TD B
Pin 5	CTS	Request To Send Pin 4 RTS B
Pin 6	DSR	Clear To Send Pin 5 CTS A'
		Data Set Ready Pin 6 CTS B'
		(connected to Data Terminal Ready) Pin 7 TD A
Pin 7	Sig Gnd	Signal Ground Pin 8 TD B
Pin 8	RLSD	Receive Line Signal Detect Pin 9 SIG RTN
Pin 9	+12VDC	Positive DC Supply Input Pin 10 RD A'
Pin 10	-12VDC	Negative DC Supply Input Pin 11 RD B'
Pin 16	Echo Sup	Echo Suppression (tie to pin 17 to enable) Pin 12 SIG RTN
		Echo Suppression (tie to pin 16 to enable)
Pin 17	Echo Sup	Data Terminal Ready (connected to Data Set Ready)
Pin 20	DTR	

Model	LDM485
Channel Lines ⁽²⁾	TD, RD, RTS, CTS
Control Lines ⁽²⁾	RTS, CTS, DTR, DSR, RLSD
Null Modem Switch	1 (Reverses RS-232 pins 2 and 3)
RS-485 Output Drive	60mA max/output
RS-485 Input Impedance	12kΩ min/input
Power: AC operation ⁽³⁾ DC operation	12VAC, ±10%, 10W screw terms 1 & 2 +11.5 to +17VDC @ 500mA on pin 9 -11.5 to -17VDC @ 100mA on pin 10
Operating Environment	0°C to +70°C, 0-95% relative humidity, noncondensing
Dimensions	53.3 mmH x 167.6 mmW x 32.5 mmD (2.1 x 6.6 x 1.28")
Weight AC Transformer	200 g (7 oz) max 311.8 g (11.0 oz) max
MTBF ⁽⁴⁾	>100,000 hrs

Notes: (2) TD = Transmit Data, RD = Receive Data, RTS = Request To Send, CTS = Clear To Send, DTR = Data Terminal Ready, DSR = Data Set Ready, RLSD = Received Line Signal Detect. (3) 120VAC and 220 VAC power transformers are available. (4) Ground-benign environmental conditions (no salt atmosphere, <50°C ambient temperature).

MOST POPULAR MODELS HIGHLIGHTED

To Order (Specify Model No.)

Model No.	Price	RS232 Connector	Power Source
LDM485-P	\$225	25 Pin male	Host-powered
LDM485-S	225	25 Pin female	Host-powered
LDM485-PT	240	25 Pin male	Transformer
LDM485-ST	240	25 Pin female	Transformer

Includes operator's manual. Transformer powered units also include 120 Vac wall mount transformer.

Ordering Example: LDM485-ST converter: \$240.

omega.co.uk[®]

Your One-Stop Source for Process Measurement and Control!

Freephone 0800 488 488 | International +44(0) 161 777 6622 | Fax +44(0) 161 777 6622 | Sales@omega.co.uk

www.omega.co.uk



UNITED STATES

www.omega.com

1-800-TC-OMEGA
Stamford, CT.

CANADA

www.omega.ca

Laval(Quebec)
1-800-TC-OMEGA

GERMANY

www.omega.de

Deckenfronn, Germany
0800-8266342

UNITED KINGDOM

www.omega.co.uk

Manchester, England
0800-488-488
+44-(0)161-777-6611

FRANCE

www.omega.fr

0800-466-342

BENELUX

www.omega.nl

0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders, Relative Humidity Measurement Instruments, PT100 Probes, PT100 Elements, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples, Thermowells and Head and Well Assemblies, Transmitters, Thermocouple Wire, RTD Probes

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485, Ethernet and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Pressure Transmitters, Strain Gauges, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters