

Portable Low Cost Datalogger

Part of the NOMAD® Family

OM-SC
\$235



OM-SC-KIT, \$465, datalogger complete with RS-232 cable and DC voltage input cable. Shown close to actual size.

- ✓ **Measures and Records DC Current, DC Voltage Temperature, Contact Closure and Ambient Light**
- ✓ **Time Extension Recording—Automatic Sampling up to 1 Year**
- ✓ **Automatic Scaling Provides for Best Resolution**
- ✓ **Easy-to-Use Windows® Software**

Whether the OM-SC datalogger records for an hour, a week or a year, by using its innovative time extension recording technique, the completed recording is at a sampling interval that is appropriate for the length of the recording session. Initially the datalogger samples every 0.88 seconds. In 2 hours, its memory is full. It then doubles its sampling interval and continues recording. After 4 hours, its memory is full again using a sampling interval of 1.76 seconds. Each time its memory fills up, the OM-SC doubles its sampling interval and repeats the process. Refer to the table above for a list of sampling intervals corresponding to various lengths of recording sessions. The OM-SC records temperature with

its internal thermistor temperature sensor or with an optional external temperature sensor. The datalogger also measures DC voltage, DC current (the OM-SC datalogger can be used to record 4 to 20 mA current loop signals and then to scale, plot, print, totalize and save the data in the process units being measured) and contact status. It is not necessary to specify the recording function in advance; you specify it when downloading to your computer.

Automatic scaling permits the OM-SC to operate over wide ranges of DC voltage and DC current signal levels. The datalogger starts recording at its lowest scale range and rescales each time the signal exceeds the scale range. Automatic scaling also functions when the OM-SC is recording temperature; it allows the datalogger's 256 steps of resolution to be used to maximum advantage. When recording temperature, the scale range is determined by the maximum temperature recorded, and the resolution is best at the top of the range. The OM-SC initially scales itself on its first reading and is limited to four scale changes after that.

The OM-SC software produces a clear, well-formatted presentation quality graph. The vertical grid lines fall on major time increments. A zoom

function permits the user to examine details in the record and select a portion of the graph for display. The graph includes the datalogger's serial number, complete date and time information, title provided by the user, sample rate, min/max and average signal readings, and the online signal reading. The finished graph can be printed or exported to other software. The data can be saved to disk and imported into common spreadsheet programs.

The operation of the datalogger is controlled by a button on the front of the unit. The mode of operation is indicated by a light to the left of the button. There are three modes of operation: RECORD, STANDBY, and SLEEP. RECORD is entered from SLEEP by a press of the button; the light makes double blinks to indicate that the datalogger is recording. STANDBY is entered from RECORD by a press of the button; it is indicated by single blinks on the light. In the STANDBY mode the datalogger does not record; it keeps time and retains data for later downloading to the computer. SLEEP is entered from RECORD or STANDBY by a long (2 seconds or more) press of the button. In the SLEEP mode the datalogger is inactive, and the light does not blink. Data can be downloaded from the datalogger only when it is in the RECORD or STANDBY modes.

Specifications

No. of Channels: 1

Input Types: Temperature via internal thermistor, DC voltage, DC current, contact closure, ambient light

Input Connection: DC voltage, DC current, contact closure, ambient light via plug-in cable

Measurement Range: DC voltage; 400 mV to 27 Vdc; DC current; 4 to 20 mA; temperature via internal sensor; 0 to 70°C (32 to 158°F); temperature via external sensor; -55 to 140°C (-67 to 284°F); contact closure; dry contacts; ambient light; 10 to 2000 lumens/sq. meter via external ambient light sensor with plug-in cable

Accuracy: DC Voltage; $\pm 1.4\%$ of scale; DC Current; ± 0.3 mA; temperature; ± 1.0 °C or better when range of recorded temperature is 0 to 70 °C; ambient light; ± 2 lumens $\pm 20\%$ of rdg

Resolution: DC Voltage; 0.4% of scale; DC Current; 0.1 mA; temperature; 0.3°C or better when range of recorded temperature is 0 to 70°C

Sample Rate: 4096/hr max

Data Storage: 8192 readings

Storage Technique:

Time extension recording

Power: 3V lithium battery

Battery Life: Up to 1 year of continuous recording at 25°C

Operating Temperature:

-20 to 70°C (-4 to 158°F)

Storage Temperature:

-40 to 85°C (-40 to 185°F)

Relative Humidity:

0 to 100% non-condensing

Dimensions:

38 H x 57 W x 21 mm D

(1½ x 2¼ x 13/16")


Weight: 28 g (1 oz)

Recording Current Loop Signals

Range	Accuracy (Including Resolution)
419 mV	± 6 mV
851 mV	± 12 mV
1.72 V	± 24 mV
3.44 V	± 48 mV
6.90 V	± 96 mV
13.8 V	± 192 mV
27.6 V	± 384 mV

Sampling

Sampling Intervals	Samples Per Hour	Length of Recording Session
0.88 seconds	4096	2 hours
1.76 seconds	2048	4 hours
3.52 seconds	1024	8 hours
7.03 seconds	512	16 hours
14.06 seconds	256	32 hours
0.47 minutes	128	2.66 days
0.94 minutes	64	5.33 days
1.88 minutes	32	10.8 days
3.75 minutes	16	3.02 weeks
7.5 minutes	8	6.1 weeks
15 minutes	4	12 weeks
30 minutes	2	5.63 months
1 hour	1	11.2 months



To Order (Specify Model Number)

Model No.	Price	Description
OM-SC-KIT	\$465	Datalogger kit*
OM-SC	235	Portable datalogger
OM-SC-C-T	45	Remote temperature input cable, 20 to 80°C
OM-SC-C-HT	45	Remote temperature input cable, 25 to 140°C
OM-SC-C-LT	45	Remote temperature input cable, -55 to 25°C
OM-SC-C-I	95	Current (4 to 20 mA) input cable
OM-SC-C-V	45	DC voltage/contact closure input cable
OM-SC-C-AL	109	Ambient light sensor
OM-SC-S-I	118	Windows software (on CD ROM) and RS-232 cable with DB9F termination

* Includes **OM-SC** datalogger, **OM-SC-C-T** (temperature input cable), **OM-SC-C-I** (4 to 20 mA input cable), **OM-SC-C-V** (DC voltage/contact closure input cable), **OM-SC-C-AL** (ambient light sensor), and **OM-SC-S-I** (Windows software and RS-232 cable)

Comes with complete operator's manual.

Ordering Example: **OM-SC** datalogger, **OM-SC-C-T** remote temperature input cable, **OM-SC-C-V** voltage/contact closure input cable and **OM-SC-S-I** Windows software and RS-232 cable, \$235 + 45 + 45 + 118 = **\$443**.

omega.co.uk[®]

Your One-Stop Source for Process Measurement and Control!

Freephone 0800 488 488 | International +44(0) 161 777 6622 | Fax +44(0) 161 777 6622 | Sales@omega.co.uk

www.omega.co.uk



UNITED STATES

www.omega.com

1-800-TC-OMEGA

Stamford, CT.

CANADA

www.omega.ca

Laval(Quebec)

1-800-TC-OMEGA

GERMANY

www.omega.de

Deckenpfronn, Germany

0800-8266342

UNITED KINGDOM

www.omega.co.uk

Manchester, England

0800-488-488

FRANCE

www.omega.fr

088-466-342

CZECH REPUBLIC

www.omegaeng.cz

Karviná, Czech Republic

596-311-899

BENELUX

www.omega.nl

0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders, Relative Humidity Measurement Instruments, PT100 Probes, PT100 Elements, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples, Thermowells and Head and Well Assemblies, Transmitters, Thermocouple Wire, RTD Probes

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Pressure Transmitters, Strain Gauges, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters